

SYNTHESIS OF MO-ZR SURFACE ALLOY BY USING A LOW-ENERGY HIGH-CURRENT ELECTRON BEAM *

E.V. YAKOVLEV, A.V. SOLOVYOV, V.I. PETROV, A.E. PESTEREV, A.B. MARKOV

Tomsk Scientific Center of the Siberian Branch of the Russian Academy of Sciences, Tomsk, Russian Federation

Zirconium-based alloys have served the nuclear industry for several decades due to their unique set of properties [1]. During normal operation, zirconium alloys form a protective layer of zirconium oxide that protects against corrosion. However, at high temperatures, which can occur under accident conditions, zirconium alloys exhibit poor oxidation kinetics [2, 3]. The developing concept of accident tolerant fuel (ATF) defines a several areas of research and development aimed at improving the safety of nuclear fuel during normal operation, transients and possible accident [3-5]. One of the areas of ATF is the development of protective coatings on the surface of zirconium [4, 5]. Coatings based on chromium are the most promising, since they meet the basic requirements for ATF coating materials for Zr fuel cladding. Chromium has a high melting point, high corrosion resistance in water and steam due to protective chromium scale, and a coefficient of thermal expansion similar to zirconium alloys [4, 5]. However, interdiffusion at the interface between the protective coating and the substrate is a serious problem. In addition, interdiffusion can degrade the adhesive properties of the coating, leading to the destruction or bulging of the coating. The easiest way to limit diffusion between the Cr coating and the Zr substrate is to add a diffusion barrier between the coating and the Zr substrate. Molybdenum is considered one of the most promising interlayer materials, as it exhibits good barrier properties, CTE close to Cr, high thermal conductivity, high melting point, and acceptable neutron cross section. Moreover, the potential eutectic phase Mo-Zr has a higher melting point (1550°C) compared to Cr-Zr (1330°C) [6, 7].

The aim of present work was to synthesize of Mo-Zr surface alloy using magnetron deposition of Mo films and consequent irradiation with a low-energy, high-current electron beam (LEHCEB).

The electron-beam machine "RITM-SP" with an explosive-emission cathode and a plasma-filled diode generating the LEHCEB was employed in the work [8]. This machine is equipped with a magnetron sputtering system enabling formation of multicomponent surface alloys. The surface alloy was formed by repeating the operations of deposition of the Mo film on the Zr substrate and following LEHCEB irradiation. The surface alloy was formed at different NEEP energy densities, which resulted in different melt thicknesses and, consequently, different elemental and structural-phase compositions of the surface layer.

The surface morphology, phase and elemental composition of the Mo-Zr surface alloys were analyzed, the microhardness and wear resistance were measured. For its characterization different techniques like SEM, XRD and others have been used. The elemental composition of both the surface and cross sections of the samples was analyzed by EDS analysis. The structure and properties of the synthesized Mo-Zr surface alloy was compared with witness-specimens, which is coatings but without LEHCEB treatment.

REFERENCES

- [1] V. Azhazha, B. Borts, I. Butenko, V. Voevodin et al., Zirconium-Niobium alloys for NPP, Alushta, Ukraine, 2012.
- [2] J.C. Brachet, E. Rouesne, J. Ribis et. al., "High temperature steam oxidation of chromium-coated zirconium-based alloys: Kinetics and process," Corros. Sci., vol. 167, Article Number 108537, 2020.
- [3] K.A. Terrani, S.J. Zinkle, L.L. Snead, "Advanced oxidation-resistant iron-based alloys for LWR fuel cladding," J. Nucl. Mater. vol. 448, pp. 420-435, 2014.
- [4] E. Kashkarov, B. Afornu, D. Sidelev et. al., "Recent advances in protective coatings for accident tolerant Zr-based fuel claddings," Coatings, vol. 11, Article Number 557, 2021.
- [5] J. Yang, M. Steinbrück, C. Tang et. al., "Review on chromium coated zirconium alloy accident tolerant fuel cladding," J. Alloys and Comp., vol. 895, Article Number 162450, 2022.
- [6] J. Houserová, J. Vřešťál, M. Šob "Phase diagram calculations in the Co-Mo and Fe-Mo systems using first-principles results for the sigma phase," Calphad Comput. Coupling Phase Diagrams Thermochem., vol. 29, pp. 133-139, 2005.
- [7] B. Cheng, Y.-J. Kim, P. Chou "Improving accident tolerance of nuclear fuel with coated Mo-alloy cladding," Nucl. Eng. Technol, vol. 48, pp. 16-25, 2015.
- [8] A.B Markov, A.V. Mikov, G.E. Ozu, A.G. Padei, Instrum. and Experim. Tech., vol. 54, pp. 862-866, 2011.

* The work was supported by the Ministry of Science and Higher Education of the Russian Federation (project № FWRP-2021-0001).